



## PS2012AB

### PS2 Series Position Sensor

#### Features

- UL listed model
- Adjustable with XY axis using appropriate magnets
- Cable wiring from the Right of the package
- Repeatability of operation
- Shunt or direct magnet operation

#### Comments

- Robust Nylon Housing
- Normally Open
- Surface Mounted by fixing screws
- Fully encapsulated
- Matching Magnet PM101 or PM102

#### Applications

- Door Interlocks
- Hook Switches
- Security Systems
- Safety Interlocks
- Position Indication

Material

Housing Material	Glass Filled Nylon 6.6
Contact Material	Ruthenium
Operating Temperature °C	-30 to 105
Housing Colour	Black

Mechanical Specifications

Shock	50g for 11ms duration
Vibration	35g up to 500Hz
IP	IP65

Switching

Switch Action (Reed Switch)	SPST
Max Switching Voltage VDC	200
Max Switching Voltage VAC	250
Max Switching Current Amps	1
Max Switching Load Watt	30
Operate Mode	Direct Axis, Parallel Axis
Contact Form	A

Cable

Cable Length	2 x 0.5M
Connection Type	Stripped Cables
Cable Type	UL1569 24AWG, 7/32mm PVC insulated
Cable Colour	Black/Black

Mounting

Fitment	Surface
Mounting	Any Axis

Technical Drawing

