



## VCS-01 VCS Series • Top or Bottom • Level Sensor

## Features

- Overall length less than 60mm
- Internal Fit
- 30mm diameter float
- Polypropylene Material

## Comments

- High or Low level sensing
- N/O or N/C by float reversal
- Reed Switch Reliability (UL File E153493)
- Exposed Magnet
- Interface Option Available

## **Applications**

- Water high or low Level
- Condensate level alarm
- Chemical high or low level
- Cooling systems
- Coolant level indication

Material		Cable	
Housing Material Float Material	Polypropylene Foamed Polypropylene	Cable Length Connection Type	2 x 0.1M Stripped Cables
Contact Material	Ruthenium	Cable Type	22 AWG 16/0.2mm PVC insulated
Float SG Medium Housing Colour Float Colour	0.64 Water Black White	Cable Colour	Black/Black
Mechanical Specifications		Mounting	
Shock	3 half-sine pulses of 11mS, 30G	Thread	1/8
Vibration Float Diameter IP	35g up to 500Hz 30mm IP65	Fitment Mounting	Internal Fit Top or Bottom entry
Switching		Technical Drawing	
Switch Action (Reed Switch) Max Switching Voltage VDC Max Switching Voltage VAC Max Switching Current Amps Max Switching Load Watt	SPST 200 250 1 30	VCS - 01	
Operate Mode	N/C with float at bottom stop		4/0    N DT
Contact Form	A	- <del>1</del>	1/8 " N.P.T

12 (0.47) Hex