



VCS-02

VCS Series • Top or Bottom • Level Sensor

Features

- Overall length less than 60mm
- Internal Fit
- 30mm diameter float
- Polypropylene Material

Comments

- High or Low level sensing
- N/O or N/C by float reversal
- Reed Switch Reliability (UL File E153493)
- Exposed Magnet
- Interface Option Available

Applications

- Water high or low Level
- Condensate level alarm
- Chemical high or low level
- Cooling systems
- Coolant level indication

VCS-02

VCS Series • Top or Bottom • Level Sensor

Material

Housing Material	Foamed Polypropylene
Float Material	Polypropylene
Contact Material	Ruthenium
Float SG	0.64
Operating Temperature °C	-30 to 70
Medium	Water
Housing Colour	Black
Float Colour	White

Cable

Cable Length	2 x 0.1M
Connection Type	Stripped Cables
Cable Type	22 AWG 16/0.2mm PVC insulated
Cable Colour	Black/Black

Mechanical Specifications

Shock	3 half-sine pulses of 11mS, 30G
Vibration	35g up to 500Hz
Maximum Pressure	1.3 Bar
Float Diameter	30mm
IP	IP65

Mounting

Thread	M8 x 1.25mm
Fitment	Internal Fit
Mounting	Top or Bottom entry

Switching

Switch Action (Reed Switch)	SPST
Max Switching Voltage VDC	200
Max Switching Voltage VAC	250
Max Switching Current Amps	1
Max Switching Load Watt	30
Operate Mode	N/C with float at bottom
Contact Form	A

Technical Drawing

VCS - 02

