



VS309-21N

VS Series—Level Sensor

Features

- High or low level sensing
- External fitting
- Reed Switch reliability
- Nitrile Sealing grommet
- Easy installation

Comments

- Normally open or normally closed by float inversion
- Suitable for a wide range of liquids
- Interface option available
- Nylon 6.6 Material

Applications

- Chemical high or low level
- Diesel Fuel
- Fuel low level
- Alcohols
- Low Oil Detection

VS309-21N

VS Series—Level Sensor

Material

Housing/Shuttle Material	Glass Filled Nylon 6.6
Float Material	Glass Filled Nylon 6.6
Contact Material	Ruthenium
Float SG	0.74
Operating Temperature °C	-30 to 130
Medium	Fuels, Oils, Alcohols
Housing and Float Color	Blue

Mechanical Specifications

Shock	50g for 11mS duration
Vibration	35g up to 500Hz
Maximum Pressure	4.7 Bar
Float Diameter	22mm
IP	IP65

Switching

Switch Action (Reed Switch)	SPST
Max Switching Voltage VDC	200
Max Switching Voltage VAC	250
Max Switching Current Amps	1
Max Switching Load Watt	70
Operate Mode	N/C with float at bottom stop
Contact Form	A

Cable

Cable Length	2 x 0.5M single insulated
Connection Type	Stripped Cables
Cable Type	22 AWG 16/0.2mm PVC insulated
Cable Color	Black

Mounting

Thread	M16
Fitment	External
Mounting	Vertical

Technical Drawing

